COOLMAX®

C U   S E R I E S

Silent Cooling Fan System:

120mm cooling fan system built with honeycomb structured ventilation for the quickest heat dissipation and lowest noise level possible.

POWER CONNECTOR

S-ATA

PCI-E

S-ATA

Peripheral Power Connector X 4

SPECIAL FEATURES:

Smart detachable cable design allows you to connect cables you actually need, therefore improve internal airflow and avoid system clutter.

A0004400
Licensed under U.S. Patents
7,133,293;
Pending

Dual PCI-e Connectors Available:

At 700 watts, this power supply has dual PCI-e connectors available for higher graphic rendered endeavors.

Partially Modular:

Have the necessary cables attached and ready while connecting only the connectors you want. Keep a clean environment with easy installation. Eliminate the clutter.

Warranty Coverage:

5 year manufacturer warranty to help ensure your satisfaction with the CU-series.

http://www.coolmaxusa.com

CU SERIES

Need a power supply that's powerful, clean, and easy to install? This is it. The CU-series can provide up to 700 watts to power your system, and at 700 watts, you will have dual PCI-E connectors for better graphic capabilities! It is also partially modular, so you can select the cables you want and keep the cables you need!

Features

- Dual PCI-E connectors (at 700W)
- Automatic fan setting for most effective cooling system
- Partially modular for a clean and easy installation and cable management
- Tri +12V output rails

- Super high efficiency above 80%
- Great balance between cooling and noise level
- 120 mm silent fan design
- All output cables with nylon sleeving
- ATX 12V V2.2/EPS 12V V2.91

Power Distribution Configuration

	AC INPUT			100~132VAC or 200~264VAC				
MODEL	DC OUPUT	+3.3V	+5V	+12V1	+12V2	+12V3	-12V	+5VSB
CU-400B	Max. Output Current	20A	18A	18A	18A	-	0.5A	2.5A
	Max. Combined	120W		320W				
CU-500B	Max. Output Current	21A	22A	17A	17A	12A	0.5A	2.5A
	Max. Combined	150W		400W				
CU-600B	Max. Output Current	24A	24A	18A	18A	15A	0.5A	2.5A
	Max. Combined	160W		450W				
CU-700B	Max. Output Current	28A	28A	18A	16A	16A	0.5A	3.0A
	Max. Combined	180W		570W				

Power Connector

CU SERIES						
Connector	20+4 pin	Periphal	SATA	FDD	PCIe 6-Pin	4 pin to 8 pin
CU-400B	1	4	4	1	1	1
CU-500B	1	4	4	1	1	1
CU-600B	1	4	4	1	1	1
CU-700B	1	4	4	1	2	1

Model Number

Model Number	UPC Barcode	Dimension (L x W x H)
CU-400B	895963147370	6.00 x 5.60 x 3.50 IN
CU-500B	895963147387	6.00 x 5.60 x 3.50 IN
CU-600B	895963147394	6.00 x 5.60 x 3.50 IN
CU-700B	895963147400	6.00 x 5.60 x 3.50 IN

Warranty: Coolmax 5 year limited warranty